

BIG-T® MECHANICAL ROTARY STEERING (SINGLE) SYSTEM

The Original Teleflex Steering System! For over 35 years, Big-T® has been the most durable, versatile mechanical steering system made, with both single and dual station capability. The heavy duty helm incorporates a strong steel pinion, dual diecast gears and meaty shaft bearing supports, all encased in a rugged gear housing. It's no wonder owners of small inboards have counted on the Teleflex Big-T since 1963!

APPLICATIONS

Inboards to 34 feet with one engine. Also suitable for sterndrive boats with power-assisted steering. Big-T systems accept steering wheels up to 20" diameter.

COMPLETE SYSTEMS	
This steering system is sold by components. Select helm, bezel and cable from items listed below.	
COMPONENTS	
Big-T Helm (single station push-pull)	SH5000P
Big-T Cable (QC II cable) Replaces SSC72XX Includes SA27620P Helm Converter	SSC61XX
Bezel 2-pc. Black (90°/20° mount)	SB27265P
OPTIONS	
Cable Gard (fits most tilt tubes)	SA39329P
SERVICE ITEMS	
Steering Wheel Hardware Kit (Old #2745417P)	SA27454P
Spent Travel Tube (Big-T)	SA35680P

Big-T®

ISSUE DATE JAN-2011 NO. MS1usa

AT A GLANCE

FEATURES

- Available in single or dual station versions.
- Responsive 3 turns from lock-to-lock.
- Standard 3/4" round tapered steering wheel shaft.
- Stainless steel cable output ends.
- 2-piece bezel for 90° or 20° helm mount to dash.
- Optional 1-piece
 90° bezel for compact mounting.
- Uses Teleflex SSC61 type cable
- Meets A.B.Y.C. standards.
- Meets N.M.M.A. certification requirements.

Page 1 of 2







BIG-T® MECHANICAL ROTARY STEERING (DUAL) SYSTEM

COMPLETE SYSTEMS		
This steering system is sold by components. Select helm, bezel and cable from items listed below.		
COMPONENTS		
Big-T Helm (single station push-pull) (2)	SH5000P	
Big-T Cable (dual station) (1)	SSC81AxxBxx *	
Bezel 2-pc. Black (90°/20° mount) (2)	SB27265P	
OPTIONS		
Cable Gard (fits most tilt tubes)	SA39329P	
SERVICE ITEMS		
Steering Wheel Hardware Kit (Old #2745417P)	SA27454P	
Spent Travel Tube (Big-T)	SA35680P	

^{*} Dual station requires purchase of special order non-returnable cable.

HOW TO MEASURE CABLE FOR DUAL STATIONTATION BIG -T:

For a Big-T dual station steering system, the cable required is SSC81AxxBxx, where xx = the lengths of the two cable sections in feet. The letter "A" in the part number represents the cable routing path distance between steering stations. The letter "B" represents the cable routing path distance from the lower station to the engine/rudder area. The different cable lengths are available in one-foot increments only.

EXAMPLE: if the cable routing from engine to lower station is 18 feet and 10 feet from station to station, order part number SSC81A10B18 cable.

CABLE MEASUREMENT: DUAL STATION

PATH "A":

CENTER LINE OF UPPER

STATION WHEEL TO

CENTER LINE OF LOWER

STATION WHEEL.

PATH "B":

CENTER LINE OF LOWER


STATION WHEEL TO

CABLE CONNECTION

AT CENTERED TILLER.

CENTERLINE OF BOATOR

CENTERED TILLER



o.



ISSUE DATE JAN-2011 NO. MS1usa

AT A GLANCE

FEATURES

- Available in single or dual station versions.
- Responsive 3 turns from lock-to-lock.
- Standard 3/4" round tapered steering wheel shaft.
- Stainless steel cable output ends.
- 2-piece bezel for 90° or 20° helm mount to dash.
- Optional 1-piece
 90° bezel for compact mounting.
- Uses one Teleflex SSC81AxxBxx steering cable.
- Meets A.B.Y.C. standards.
- Meets N.M.M.A. certification requirements.

Page 2 of 2



